



EBARA

Submersible Sewage/Wastewater Pumps

Model DSC4/DSCA4



water | wastewater | sewage | flood control



EBARA

EBARA Fluid Handling

an EBARA International Corporation company

Model DSC4/DSCA4


Features

- **New! 32 enclosed impeller models with extended hydraulics, higher horsepowers, higher flows, larger discharge and suction sizes, and ICS options now available!**
- **Watertight cable entry system with redundant protection** assures safe operation and protects against water leakage into terminal casing; reduces maintenance costs
- **Terminal board provides easy cable connection**
- **Heavy duty, high efficiency, compact designed motor** with thermal detector for each phase of winding; inverter duty rated and FM approved
- **Self cooling system with cooling jacket** eliminates the need for external pumping devices or special heat transfer fluids; offers simplicity and high reliability by effectively dissipating heat, **ICS option available** for 4P/6P 50-145 HP models
- **Float type leakage detector** provides early warning of mechanical seal failure; avoids costly motor repairs
- **Cartridge type*, duplex mechanical seals** assembled in tandem arrangement; easy maintenance and high reliability (*standard models)
- Available with semi-open or enclosed impellers

Standard Specifications

Design	Discharge Horsepower Capacity Total head Max. Liquid temp.	6 to 20 inch 50 to 245 530 to 12500 USGPM (2 to 48 m ³ /min) 12 to 300 ft (3.8 to 91 m) 104°F/40°C
Materials	Casing Impeller Casing Ring Shaft Motor Frame Cooling Jacket Fastener	Cast Iron Cast Iron 420 Stainless Steel (enclosed impeller models) 420 Stainless Steel (4P/6P 50-145HP models) 403Q Stainless Steel (4P/6P/8P 175-245HP, 10P 50-145HP models) Cast Iron Steel 304 Stainless Steel
Construction	Impeller Type Shaft Seal Material – Upper Material – Lower Bearing Motor Mounting method	Semi-open Enclosed <i>Optional:</i> Impeller Ring (enclosed impeller models) Cartridge type* duplex mechanical seals in tandem arrangement (*available on standard models) Carbon/Ceramic Silicon Carbide/Silicon Carbide <i>Optional materials available, consult factory.</i> Grease Lubricated Ball Bearing Class H insulation Air filled water tight with cooling jacket 15 starts/hour : 4P/6P 50-145HP 10 starts/hour : 4P/6P/8P 175-245HP, 10P 50-145HP <i>Optional:</i> FM explosion proof, Class 1, Group C, D Built-in winding temperature detector Built-in float type leak detector <i>Optional:</i> Temperature detector for thrust bearing Wet Pit: Quick discharge connector (QDC) Dry Pit: with baseplate (DSCA4)
Accessories		50 ft (15.24 m) water tight rubber insulated flexible cable <i>Optional cable lengths available.</i>

DSC4/DSCA4 selection chart



EBARA Fluid Handling

1651 Cedar Line Drive • Rock Hill, SC 29730 • t (803) 327 - 5005 • f (803) 327 - 5097

www.pumpsebara.com

© 2011 EBARA International Corporation, All rights reserved.

* All specifications subject to change without notice.

EFHDSC40415