



Product Name: **Stainless Submersible Sump Pump**

Model Number: **DCM50**

Manufacturer: **PumpBiz Pumps**

Stainless Steel Sump Pump, submersible SS pump 1/2HP. Heavy duty submersible pump for sumps, construction sites, parking lots, industrial waste waters wherever the 304SS offers increased corrosion protection and dependable operation is needed. Chemical resistant sump pump for use with nonflammable liquids compatible with pump materials.

Dewatering, submersible utility, corrosion resistant sump pump.

[RFQ](#)

[ASK CHARLIE](#)

[SEND TO A FRIEND](#)

Rating: ★★★★★

Usual Ship Time:

Your Price: **\$729.00 EA**

[Add to Cart](#)

Product Specifications

Images/Other

Related Accessories

| | |
|---------------------------------|------------------------|
| Maximum Flow | 75 gallons/min |
| BEP Flow | 51 gallons/min |
| TDH Maximum PSI @ 0GPM | 36 PSI |
| TDH BEP | 15 psi |
| HP Standard | 0.5 HP |
| Outlet Connection Type | FNPT |
| Outlet | 2 " |
| Wetted Materials | 304SS |
| Elastomers | Viton |
| Length | 14 " |
| Voltage | 115 V |
| Phase | 1 |
| Frequency | 60 Hz |
| Motor | Hermetically Sealed |
| Motor Amps | 4.7 A |
| Speed | 3450 RPM |
| MTR Cord Length | 20 FT |
| Motor Cord Size | 16/3 |
| Max Operating Temp | 104 °F |
| Viscosity | Milk 3.20 cp 40.00 ssu |
| Max. Particle Size | 0.25 " |
| Max Specific Gravity | 1 sp. gr. |
| Max. Particle Hardness | 5 MOH |
| Max. Volume of Suspended Solids | 5 % |
| Shaft | 304SS |
| Mechanical Seal Face | Carbon-ceramic |
| Mechanical Seal Type | Double |

| | |
|-----------------------|--------------------------|
| Impeller Mat'l / Type | 304SS |
| Warranty | 1 Year/s |
| Applications | Chemical |
| | Contractor |
| | Dewatering |
| | Fountain |
| | Parts Washer |
| | Submersible |
| | Sump |
| PH Low | 4 pH |
| PH High | 9 pH |
| Other | Pump max. diameter 8.7". |
| Approvals | US-CSA |
| Country of Origin | Taiwan |
| Duty | Continuous |
| Weight | 24 lbs |